



# FARMALL® UTILITY A

SERIES TRACTOR

SPECIFICATIONS



# FARMALL UTILITY A SERIES TRACTOR SPECIFICATIONS

MODEL	FARMALL 55A	FARMALL 65A	FARMALL 75A
Operator Station		Cab	Cab / Non-cab
Traction		2WD / MFD	
<b>ENGINE</b>			
Type	Tier 4 B/Final with 3-cylinder, FPT turbocharged & aftercooled		
Displacement	178.8 in <sup>3</sup> (2930 cm <sup>3</sup> )		
Engine HP*	54 HP	64 HP	74 HP
PTO HP*	43 HP	51 HP	60 HP
Emissions Treatment	External cooled exhaust gas recirculation (CEGR) with diesel oxidation catalyst (DOC)		
Fuel System	Electronic high pressure common rail		
Fuel Capacity	21.7 gal. (82 L)		
Alternator	120 amp		
<b>TRANSMISSION</b>			
Standard	8 × 8 mechanical shuttle		
Optional	12 × 12 power shuttle or 12 × 12 with creeper		
Differential Lock	Mechanical		
MFD Engagement	Electro-hydraulic		
<b>3-POINT HITCH FEATURES</b>			
3-Point Hitch Category	Cat II/I		
Draft Sensing or Lift Control	Top link sensing		
<b>3-POINT HITCH LIFT CAPACITY</b>			
Standard Lift Capacity @ 24 in. Behind Pin	4,299 lb. (1 950 kg)		
Optional Lift Capacity @ 24 in. Behind Pin	4,740 lb. (2 150 kg)		
<b>AXLES</b>			
Front	2WD or MFD with limited slip		
Rear	Flange		
<b>PTO</b>			
PTO Speed (Standard / Optional)	540 @ 1,957 engine rpm / 540/540E @ 1,592 engine rpm		
<b>HYDRAULICS</b>			
System Type	Open center		
Number of Rear Remotes	2-3		
Hydraulic Pump / Flow	Fixed Displacement / 12.6 gal./min. (47.7 L/min.)		
<b>DIMENSIONS &amp; WEIGHTS</b>			
Wheelbase (2WD / MFD)	81.2 in. (2 063 mm) / 81.8 in. (2 078 mm)		
Overall Length**	151.8 in. (3 856 mm)		
Overall Height (2WD)	98 in. (2 495 mm)		
Overall Height (MFD)	100 in. (2 545 mm)		
Tractor Weight without Ballast (Cab / Non-cab 2WD)	6,173 lb. (2 800 kg) / 5,622 lb. (2 550 kg)		
Tractor Weight without Ballast (Cab / Non-cab MFD)	6,834 lb. (3 100 kg) / 6,283 lb. (2 850 kg)		
<b>BALLAST</b>			
Front Weights (Optional)	Qty 8 × 66 lb. (30 kg) = 528 lb. (240 kg) total		
Rear Weights (Optional)	Qty 4 × 110 lb. (50 kg) = 440 lb. (200 kg) total		
<b>TIRES</b>			
Standard (2WD / MFD)	Front: 9.5L-15 Rear: 16.9R 28Ag Tread - (R-1W) Radial / Front: 11.2 × 24 Ag Tread (R-1) Bias Ply Rear: 16.9 × 30 Ag Tread (R-1) Bias Ply		
Optional (2WD / MFD)	Front: n/a Rear: 12.4R20Ag, Tread (R-1W) Radial / Front: n/a Rear: 16.9 × 28Ag Tread (R-1W) Radial		

\*At 2,300 ERPM rated engine speed

\*\*Distance from front weights to end of 3 point hitch

SAFETY NEVER HURTS!<sup>TM</sup> Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2018 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH Industrial America LLC, are the property of those respective companies. Printed in U.S.A. www.caseih.com CIH18062903

